



ORIGINAL OAK  
FLOORS CO.

## Technical information

### Usage Result

	Product reference	Original Oak Floors Co-Prestige Series
	Size (length x width x thickness/top)	290x2450x14.2/3.2mm
	Board Type	Tongue and groove
	Pattern	1 strip
	Edging	Micro bevel
	Pack Size	2.842sqm
	Pack Weight	22kg
	Pack Length	2450mm
	Top Layer (Lamella)	3.2mm French Oak
	Surface Finish	Natural Bona UV Lacquer
	Environmental Rating	A+ Green Building Council of Australia: Pass
	Maintenance	As per maintenance instructions – refer website

### Installation methods

	Fully Bonded	Yes*
	Nailed	No
	Floating on underlay	Yes*
	Over under slab heating	Yes*

### Test information & others

	Origin	France
	EUTR	Legally Harvested Timber
	FSC	Available on request
	Floor Score	Available on request
	JANKA Janka Hardness Rating	7.0
	Slip Testing	AS/NZS 4586-2.13 D1, friction result = 0.59
	Australian reaction to fire – FLOOR	AS/ISO 9239-1:2003 CRF: 3.6kw/sqm, smoke value 21%
	Australian reaction to fire – WALL	AS/NZS 3837:1998 40.7kw/sqm
	Cigarette Burns	Repairable
	Release of Formaldehyde	ASTM D5116:2017 0.037mg/sqm/hr (max limit <0.1mg/sqm/hr)
	Swell Test	AS/NZS 4266.8:2004 = 0%, PASS (max limit 15%)
	Total VOC	ASTM D5116:2017 0.019mg/sqm/hr (max limit <0.5mg/sqm/hr)
	Warranty – Domestic	20 year wear, lifetime structural
	Warranty – Commercial	10 year wear, lifetime structural

## Installation & Warranty

All Original Oak floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. Original Oak Floors Warranty will only apply to floors which have been installed according to the Original Oak Floors Installation instructions available in each box of Original Oak Floors and on the Original Oak website.

Please note this technical sheet was written by Original Oak Floors Co Ltd, All the information is specified correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.



ORIGINAL OAK  
FLOORS CO.

[info@originaloakfloors.com.au](mailto:info@originaloakfloors.com.au)  
Ph: 1300 936 233  
[originaloakfloors.com.au](http://originaloakfloors.com.au)